

ONTARIO REGULATION 512/97

Column 1			Column 2	
Service Brake Chambers			Push Rod Travel	
Clamp Type Brake Chamber Data				
Type	Outside Diameter			
6	4½"	(114.3mm)	1¼"	(31.75mm)
9	5¼"	(133.35mm)	1⅜"	(34.93mm)
12	5 ¹¹ / ₁₆ "	(144.46mm)	1⅜"	(34.93mm)
12 Long Stroke	5 ¹¹ / ₁₆ "	(144.46mm)	1¾"	(44.45mm)
16	6 ³ / ₈ "	(161.93mm)	1¾"	(44.45mm)
16 Long Stroke	6 ³ / ₈ "	(161.93mm)	2"	(50.8mm)
20	6 ²⁵ / ₃₂ "	(172.24mm)	1¾"	(44.45mm)
20 Long Stroke	6 ²⁵ / ₃₂ "	(172.24mm)	2"	(50.8mm)
24	7 ⁷ / ₃₂ "	(183.36mm)	1¾"	(44.45mm)
24 Long Stroke	7 ⁷ / ₃₂ "	(183.36mm)	2"	(50.8mm)
24 Long Stroke with Square Inlet Port or with Square Raised Embossment on Lid	7 ⁷ / ₃₂ "	(183.36mm)	2½"	(63.5mm)
30	8 ³ / ₃₂ "	(205.58mm)	2"	(50.8mm)
30 Long Stroke with Square Inlet Port or with Square Raised Embossment on Lid	8 ³ / ₃₂ "	(205.58mm)	2½"	(63.5mm)
36	9"	(228.6mm)	2¼"	(57.15mm)
Bolt Type Chamber Data				
Type	Outside Diameter			
A	6 ¹⁵ / ₁₆ "	(176.21mm)	1⅜"	(34.93mm)
B	9 ³ / ₁₆ "	(233.36mm)	1¾"	(44.45mm)
C	8 ¹ / ₁₆ "	(204.79mm)	1¾"	(44.45mm)
D	5¼"	(133.35mm)	1¼"	(31.75mm)
E	6 ³ / ₁₆ "	(157.16mm)	1⅜"	(34.93mm)
F	11"	(279.4mm)	2¼"	(57.15mm)
G	9 ⁷ / ₈ "	(250.83mm)	2"	(50.8mm)
Rotochamber Type Chamber Data				
Type	Outside Diameter			
9	4 ⁹ / ₃₂ "	(108.74mm)	1½"	(38.1mm)
12	4 ¹³ / ₁₆ "	(122.23mm)	1½"	(38.1mm)
16	5 ¹³ / ₃₂ "	(137.32mm)	2"	(50.8mm)
20	5 ¹⁵ / ₁₆ "	(150.81mm)	2"	(50.8mm)
24	6 ¹³ / ₃₂ "	(162.72mm)	2"	(50.8mm)
30	7 ¹ / ₁₆ "	(179.39mm)	2¼"	(57.15mm)
36	7 ⁵ / ₈ "	(193.68mm)	2¾"	(69.85mm)
50	8 ⁷ / ₈ "	(225.43mm)	3"	(76.2mm)
Tie Rod Piston Type Chamber Data				
Type	Outside Diameter			
30 Long Stroke with Square Inlet Port	6½"	(165.1mm)	2½"	(63.5mm)
DD-3 Type Chamber Data				
Type	Outside Diameter			
30	8 ¹ / ₈ "	(206.37mm)	2¼"	(57.15mm)